

UR16e technical details



Specifications

Payload	16 kg (35.3 lbs)
Reach	900 mm (35.4 in)
Degrees of freedom	6 rotating joints
Programming	12 inch touchscreen with polyscope graphical user interface

Performance

Certifications	EN ISO 13849-1, PLd Category 3, and EN ISO 10218-1	
Force Sensing, Tool Flange	Force, x-y-z	Torque, x-y-z
	Range	160.0 N 10.0 Nm
	Precision	5.0 N 0.2 Nm
	Accuracy	5.5 N 0.5 Nm
Power, consumption, maximum average	585 W	
Safety	17 configurable safety functions	

Movement

Pose Repeatability per ISO 9283	± 0.05 mm	
Axis movement	Working range	Maximum speed
	Base	± 360° ± 120°/s
	Shoulder	± 360° ± 120°/s
	Elbow	± 360° ± 180°/s
	Wrist 1	± 360° ± 180°/s
	Wrist 2	± 360° ± 180°/s
	Wrist 3	± 360° ± 180°/s
Typical TCP speed	1 m/s (39.4 in/s)	

Features

IP classification	IP54	
ISO 14644-1 Class Cleanroom	5	
Noise	Less than 65 dB(A)	
Robot mounting	Any Orientation	
I/O ports	Digital in	2
	Digital out	2
	Analog in	2
Tool I/O Power Supply Voltage	12/24 V	
Tool I/O Power Supply	2 A (Dual pin) 1 A (Single pin)	

Physical

Footprint	Ø 190 mm
Materials	Aluminium, Plastic, Steel
Tool (end-effector) connector type	M8 M8 8-pin
Cable length robot arm	6 m (236 in)
Weight including cable	33.1 kg (73 lbs)
Operating temperature range	0-50°C
Humidity	90%RH (non-condensing)

Control box

Features

IP classification	IP44	
ISO 14644-1 Class Cleanroom	6	
Ambient temperature range	0-50°C	
I/O ports	Digital in	16
	Digital out	16
	Analog in	2
	Analog out	2
Quadrature Digital Inputs	4	
I/O power supply	24V 2A	
Communication	500 Hz Control frequency	
	Modbus TCP	
	PROFINET	
	Ethernet/IP	
	USB 2.0, USB 3.0	
Power source	100-240VAC, 47-440Hz	
Humidity	90%RH (non-condensing)	
Physical	Control box size (WxHxD)	475 mm x 423 mm x 268 mm (18.7 in x 16.7 in x 10.6 in)
	Weight	12 kg (26.5 lbs)
Materials	Powder coated steel	

Teach pendant

Features

IP classification	IP54	
Humidity	90%RH (non-condensing)	
Display resolution	1280 x 800 pixels	
Physical	Materials	Plastic, PP
	Weight including 1m of TP cable	1.6 kg (3.5 lbs)
Cable length	4.5 m (177.17 in)	



UNIVERSAL ROBOTS

universal-robots.com

5430 Data Ct STE 300 Ann Arbor, MI 48108
1-800-GOCOBOT
ur.na@universal-robots.com