



Powers-All ATF D/M

DESCRIPTION: Powers-All ATF D/M is a high quality automatic transmission fluid formulated with premium base stocks and advanced additive technology. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in certain other applications such as power steering units, rotary screw compressors & some hydraulic fluid applications.

BENEFITS: Powers-All ATF D/M (Automatic Transmission Fluid) provides the following benefits:

- Resists foaming
- Excellent wear protection
- Red color for easy identification
- Outstanding oxidation resistance
- Very good low temperature performance providing good cold start shifting

APPLICATION: Powers-All ATF D/M is recommended for pre-2006 model General Motors automatic transmissions where a now obsolete DEXRON[®] III fluid is specified and post-1981 and pre-2007 Ford automatic transmissions where a now obsolete MERCON[®] fluid is specified. **Not** for use in applications calling for DEXRON[®] VI or MERCON[®] V fluids or in select transmission applications requiring specialized fluids. It is suitable for use where Allison C-4 and Caterpillar TO-2 fluids are required.

TYPICAL PROPERTIES:

Powers-All ATF D/M

Product Code	Test Method	PA332022
Gravity, API	ASTM D1298	32.8
Specific Gravity	ASTM D4052	0.861
Viscosity, cSt @ 40°C	ASTM D-445	34.3
Viscosity, cSt @ 100°C	ASTM D-445	7.1
Viscosity Index	ASTM D-2270	168
Brookfield Viscosity, cP @ -40°C	ASTM D-5293	17,250
Pour Point, °F	ASTM D-5949	-46
Flash Point, COC, °F	ASTM D-92	424

**Note: Values shown are typical only and do not constitute a specification. Minor variations in product are to be expected in normal manufacturing. Always confirm with the original manufacturer's recommendation for proper equipment operating requirements.*



40 South Fifth Street Waterbury CT 06708
247 Northampton Street Easthampton MA 01027