

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier:** Powers-All Marine NS Hydraulic Oil 32, 46, 68  
**Other means of identification:** Zinc Free Anti-wear Hydraulic Fluid  
**SDS Number:** PA334932  
**CAS Number:** Blend  
**CHEMTREC:** EMERGENCY CONTACT 1-800-424-9300

**Details of the supplier of the safety data sheet:**  
 LF Powers Co, Inc.  
 40 South 5<sup>th</sup> St  
 Waterbury, CT 06708  
 TECHNICAL CONTACT NUMBER: 1-800-624-5654  
 www.info@lfpowers.com

**2. HAZARDS IDENTIFICATION**

**2. HAZARDS IDENTIFICATION**

<b>Classified Hazards</b> This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.	<b>Other Hazards</b> None Known
---	------------------------------------

**Label Elements**

No classified hazards

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS	Concentration
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	>95%
Non-Hazardous material	VARIOUS	<5%

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

**4. FIRST AID MEASURES**

**INHALATION FIRST AID:** If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.  
**SKIN CONTACT FIRST AID:** Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.  
**EYE CONTACT FIRST AID:** Flush with water for several minutes. If effects occur, consult a physician.  
**INGESTION FIRST AID:** Rinse mouth with water. If symptoms develop, obtain medical attention.

**5. FIREFIGHTING MEASURES**

**NFPA 704 Hazard Class**

**Health:** 1      **Flammability:** 1      **Instability:** 0



0 (Minimal)  
 1 (Slight)  
 2 (Moderate)  
 3 (Serious)  
 4 (Severe)

**Flash Point Minimum:** 400°F / 204°C  
**Flash Point Test Method:** Cleveland Open Cup (COC)

# Powers-All Marine NS Hydraulic Oil SDS - Safety Data Sheet

**Extinguishing Media:** Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

**Specific hazards arising from the chemical:**

**Unusual Fire & Explosion Hazards:** This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

**Special protective actions for firefighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Property Including Flash Point

## 6. ACCIDENTAL RELEASE MEASURES

Contain spilled material.  
Collect in suitable and properly labeled containers.  
Pick up excess with inert absorbent material.  
Keep away from drains and ground water.

## 7. HANDLING AND STORAGE

**HANDLING PRECAUTIONS:**

Avoid contact with eyes, skin, or clothing.  
Keep away from sources of ignition.  
Handle with care and avoid spillage on the floor (slippage).

**STORAGE REQUIREMENTS:**

Keep away from sources of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

**PERSONAL PROTECTIVE EQUIPMENT:**

Use of safety glasses and gloves are recommended.

Chemical Name	ACGIH	OSHA	Other
Distillates, petroleum, hydrotreated heavy paraffinic	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if generated	TWA: 5 mg/m <sup>3</sup> (as Oil Mist, if generated)	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Data represents typical values and are not intended to be specifications.

Appearance: Amber  
Physical State: Liquid

Viscosity: 5.0-9.0 cSt @ 100°C; 30.0-73.0 cSt @40°C  
Solubility: Nil in water  
Flash Point: >400°F / >204°C

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** Not chemically reactive.

**CHEMICAL STABILITY:** Stable under normal ambient and anticipated conditions of use.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous reactions not anticipated.

**CONDITIONS TO AVOID:** Avoid all possible sources of ignition. Extended exposure to high temperatures can cause decomposition.

**INCOMPATIBLE MATERIALS:** Avoid contact with strong oxidizing agents and strong reducing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Not anticipated under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.

No test data available on product.

No component is listed as a carcinogen, mutagen, or teratogen.

LD50/LC50 – No data available.

## 12. ECOLOGICAL INFORMATION

Avoid exposing to the environment, no specific aquatic data available.

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

Do not flush to surface water or drains.

## 14. TRANSPORTATION INFORMATION

Not regulated by DOT

## 15. REGULATORY INFORMATION

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

## 16. OTHER INFORMATION

### Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**END OF SDS**

Issue Date: 26-Nov-2018  
Revision Date: 26-Nov-2018  
Revision Note: New format