



# FULL SYNTHETIC dexos1™ MOTOR OILS

## POWERS-ALL FULL SYNTHETIC DEXOS

### FEATURES

Specially formulated with Synthetic base oils and high-performance additive components to meet the requirements of GM's rigorous dexos1™ standards.

Optimized for SQ/GF-7A Performance Standards while maintaining all the properties for backwards compatibility to all previous applicable API S and G (ILSAC) Performance Categories

Designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure.

### OEM SPECIFICATIONS

ALL VISCOSITY GRADES - API SQ/ILSAC GF-7A CHRYSLER MS-6395  
SAE 0W-20 - dexos1™ Approved · FORD WSS-M2C972-A1 · HONDA · TOYOTA · MAZDA  
SAE 5W-30 - dexos1™ Approved · FORD WSS-M2C971-A1

### TYPICAL PROPERTIES

PRODUCT CODES	PA3302129	PA3302289
SAE Viscosity Grade	0W-20	5W-30
Viscosity, cSt @ 100° C	8.0	10.2
Viscosity, CCS, cP @° C max	6,200 (-35)	6,600 (-30)
Pumping Vis, cP max	60,000	60,000
Flash Point, COC, °C, min	200	200
Density @ 15°C	0.87	0.87

 ENHANCED FUEL ECONOMY

 IMPROVED WEAR PROTECTION

 ENHANCED ENGINE DURABILITY

