



POWERS-ALL SYNTHETIC BLEND ENGINE OILS

POWERS-ALL SYNTHETIC BLEND

FEATURES

Specially formulated with both Synthetic and Group II base oils along with high-performance additive components

Optimized for SQ/GF-7A Performance Standards while maintaining all the properties for backwards compatibility to all previous applicable API and ILSAC Performance Categories (where applicable)

Designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure.

OEM SPECIFICATIONS

SAE 5W-20 - API SQ · GF-7A · CHRYSLER MS-6395 · FORD WSS-M2C970-A1
SAE 5W-30 - API SQ · GF-7A · CHRYSLER MS-6395 · FORD WSS-M2C971-A1



ENHANCED FUEL ECONOMY



IMPROVED WEAR PROTECTION



ENHANCED ENGINE DURABILITY

TYPICAL PROPERTIES

PRODUCT CODES	PA3301329	PA3301339
SAE Viscosity Grade	5W-20	5W-30
Viscosity, cSt @ 100° C	8.9	10.1
Viscosity, CCS, cP @ ° C max	6,600 (-30)	6,600 (-30)
Pumping Vis, cP max	60,000	60,000
Flash Point, COC, °C, min	200	200
Density @ 15°C	0.87	0.87