

Houghton Chemical Corporation

52 Cambridge Street • Allston (Boston) • MA 02134

Phone: (800) 777-2466 • Fax: (617) 254-2713

www.houghton.com



Green Mountain® Extended Life Product Data Sheet

Inhibited Propylene Glycol Extended Life Antifreeze/Coolant

Low toxicity antifreeze and summer coolant (Universal Formula Pre-charged for Heavy Duty Use/Universal Formula)

For health and safety information for this product, contact Houghton for a Safety Data Sheet (SDS).

Green Mountain® Extended Life Typical Properties by Concentration

Typical Properties	Conc. (~volume of EG) Item #1523	50%(~v/v of PNT) Item #1517	30%(~v/v of PNT) Item #
Propylene Glycol	91.5	45	27
Performance Additives and Water	8.5	55	73
Color	Gold	Gold	Gold
Clarity	Clear	Clear	Clear
Specific Gravity (15/15°C 60/6°F)	1.04-1.06	1.03-1.04	1.02-1.03
pH 50%	7.0-9.0	7.0-9.0	7.0-9.0
Reserve Alkalinity (min)	3	1	1
Freeze Point (°F) Max	n/a	-22	+10

Typical properties, not to be construed as specifications. As use conditions are not within its control, Houghton does not guarantee results from use of the information or products herein; and gives no warranty, express or implied.

Use Recommendation: Green Mountain® Extended Life meets or exceeds performance requirements for both automotive and Heavy Duty cooling systems, including those with aluminum heat-rejecting components such as aluminum cylinder heads, water pumps and radiators. It provides corrosion protection for all cooling system metals and is formulated to be compatible with antifreeze/coolants of all major producers. It is SCA pre-charged with nitrite to protect heavy duty truck engine cooling components such as wet sleeve liners.

Green Mountain® Extended Life antifreeze/coolant should not be used in concentrated form in your vehicle. A 50% dilution is generally recommended for best balanced protection against corrosion and summer boiling. Do not dilute to less than 33-1/3%. (Maximum freeze protection is at 70% if required.) Water quality can be an important factor affecting the long-term corrosion protection of any antifreeze. Use only water of good quality (see ASTM D3306, General Requirements for water quality). Test coolant annually or at maintenance intervals, replace when depleted or, if testing is not done, replace every two years. For HVAC systems, recreational vehicles, and protection of other Hydronic systems, please consult the heat transfer fluids section of our website or call us for suggestions.

Formulated to Satisfy: ASTM D5216 and the corrosion limits in ASTM D3306, ASTM D4985, and ASTM D6210, SAE/J1034, SAE/J1941, and Federal Specification OA548D; satisfying both Hot Surface Aluminum protection requirements of ASTM test D4340 and Cummins Heavy Duty Low Silicate requirements, and is designed to meet the requirements of TMC RP-330, GM1825M, GM1899M, Chrysler MS7170, and Ford ESEM97B44A.

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Date Revised: 3 July 2019

w:\lab\admin\product data sheets\antifreeze\green mountain extended life product data 190703.docx

Page 1 of 1